Sept. 6, 1949.

M. T. BENNER ET AL

2,481,067





UNITED STATES PATENT OFFICE

2,481,067

TIME PERIOD INDICATOR

Mark T. Benner and Jules B. Fortier, Pittsburgh, Pa.

Application December 31, 1946, Serial No. 719,378

1 Claim. (Cl. 235-88)

This invention relates to an indicator, and important objects and advantages thereof are to provide a device of the character described, which is conveniently operable to designate and visibly display the days of the month between starts of menstrual periods that a woman is most susceptible to conception in accordance with the consensus of the best medical authorities, which is adaptable to menstrual time period differentials, which is simple in its construction and arrange- 10 ment, durable, compact, readily understandable, attractive in appearance, and comparatively economical in its manufacture.

1

With the foregoing and other objects in view which will appear as the description proceeds, the 15 invention resides in the novel construction, combination, and arrangement of parts herein specifically described and illustrated in the accompanying drawing, but it is to be understood that the latter is merely illustrative of a preferred em- 20 bodiment of the invention, and that changes in the form, proportions, and details of construction may be resorted to that come within the scope of the claims hereunto appended.

In the drawing wherein like numerals of reference designate corresponding parts throughout the several views:

Figure 1 is a top plan view of a time period indicator constructed in accordance with the invention.

Figure 2 is a fragmentary side or edge view thereof.

Figure 3 is a top plan view of the operating disk embodied in the invention.

Figure 4 is a top plan view of the base disk. Referring in detail to the drawing, which is approximately full-size, the improved time period indicator comprises a flat base disk I and a flat operating disk 2. The disks may be constructed of Celluloid, or of any other suitable 40 rows, consecutively intervening between the nuable.

The operating disk 2 is mounted flatly on the top of the base disk I, and is revolubly secured to the latter, for manually adjustable frictional ro- 45 dow and said slot. tation, by a pivoting pin 3, which extends through the diametric centers of the disks. The diameter of the base disk is preferably slightly greater than the diameter of the operating disk to facilitate the adjustment of the latter on the base disk for 50 the purposes to be described.

The top surface of the base disk | is printed with four circular rows of numerals, which rows are respectively indicated at 4, 5, 6, and 7. The rows

2

larly spaced relation to each other, and each row of numerals represents the days of a full month. The inner row 4 comprises the consecutively arranged numerals from one to twenty-eight; the row 5 comprises the numerals from one to twentyб nine; the row 5 comprises the numerals from one to thirty, and the row 7 comprises the numerals from one to thirty-one.

The top surface of the operating disk 2 is printed with a plurality of concentrically arranged lines $\mathbf{8}$, which divide the top surface of the operating disk into four correspondingly arranged circular zones, respectively indicated at 9, 10, 11, and 12. Each of the zones is provided with an

elongated slot 13, which is curved to conform to the concentric arrangement of respective zones. Each of the zones is further provided with a window 14, which is disposed rearwardly of and in spaced relation to the associated slot 13. The terms "rearwardly" and "forwardly" are herein applied relatively to the direction of rotation of the operating disk 2 on the base disk 1, which is in the clockwise direction, as clearly indicated by an arrow 15 printed in each of the zones between the window 14 and the associated slot 13. 25 The slot and window of each of the zones is disposed in exact registration with respective numeral rows 4, 5, 6, and 7 on the base disk, and portions of said numeral rows are always visible through said slots and windows, as clearly illus-30trated in Figure 1.

The length of each of the slots is such that only nine consecutive numerical designations, of any of the rows 4, 5, 6, and 7, are visibly displayed 35 through said slots in respective zones 9, 10, 11, and 12, at any one time. The size of the windows 14 allows the visible display of only one numerical designation of respective rows, at any one time. Eight numerical designations, of each of the merical designation displayed in the window 14 and the first numerical designation displayed in the associated slot 13, are covered by that portion of respective zones intervening between said win-

The indicia "28 day month" is printed on the surface of the operating disk 2 in zone 9; the indicia "29 day month" is printed in zone 10; the indicia "30 day month" is printed in zone 11, and the indicia "31 day month" is printed in zone 12.

In practice, the use of the improved time period indicator is as follows: Assuming that the menstrual period of the user begins in any of the months of the year having thirty-one days, of numerals are arranged concentrically in regu- 55 namely, January, March, May, July, August,

3

October, or December, she will employ the zone designated "31 day month," which is zone 12 to determine the days of the month that she is most susceptible to conception. Supposing the menstrual period begins on the 12th day of the month, ñ she will adjust the operating disk 2 on the base disk | to bring the window 14 in zone 12 into registration with numerical designation 12 in the numerical row 7, as clearly shown in Figure 1. When the operating disk is so adjusted, the nu- 10 merical designations 21, 22, 23, 24, 25, 26, 27, 28, and 29, of said row 7, will be visibly displayed through the slot 13 in zone 12, as illustrated in Figure 1, and such displayed numerical designations are the days of the month on which she 15 is most susceptible to conception. The other zones 9, 10, and 11 are employed in the same manner for respective day months.

The present invention provides a most efficient device of its kind, which may be successfully em- 20 ployed for the benefit and assistance to women who practice so-called "rhythm systems," well known in the art to which the invention appertains.

What we claim is:

An indicator of the class described, comprising a flat base disk displaying four spaced concentrically arranged rows of consecutively disposed numerical designations, each of said rows of numerical designations representing the days 30 of a full month and varying in the number of numerical designations with respect to any other of said rows of numerical designations, and a flat operating disk mounted on said base disk and being revolubly connected to the latter, the top 35 surface of said operating disk being divided by

lines into four concentrically arranged zones, each of said zones being provided with a pair of spaced openings disposed in registration with respective rows of numerical designations, one opening of said pair of openings being of a size allowing the display of but one numerical designation therethrough at any one time and the other opening being of a size allowing the display therethrough of nine consecutive numerical designations at any one time, the space intervening between each pair of said associated openings being of a length to conceal the eight consecutive numerical designations disposed between the adjacent ends of each pair of associated openings, each of said zones displaying indicia designating different day months, and each of said zones displaying an arrow designating the direction of rotation of said operating disk on said base disk.

MARK T. BENNER. JULES B. FORTIER.

REFERENCES CITED

The following references are of record in the **25** file of this patent:

UNITED STATES PATENTS

Number	Name Date
1 042 754	Heyssler Jan. 9, 1934
9 076 942	Marquis Apr. 6, 1937
2,010,212	Gronvold Oct. 21, 1937
2,098,622	Gronvold Nov. 9, 1937
	FOREIGN PATENTS
Number 139.063	Country Date Austria May 15, 1934